

ECO-BLOCK STANDARD EXPANDED  
POLYSTYRENE FORM USING  
100mm CONNECTORS

100mm REINFORCED CONCRETE CORE

EXTERIOR BUILDING FINISH  
AS SPECIFIED

100mm PLASTIC CONNECTOR.

INTERIOR FINISH  
AS SPECIFIED

CUT OUT FORMS  
AS NECESSARY TO  
MATCH ANCHOR BOLT SPACING

SUBFLOOR

WOOD FLOOR TRUSS  
AS SPECIFIED

LEDGER BOARD/WHALING PLATE SECURED  
TO WALL WITH ANCHOR BOLTS  
AS SPECIFIED

HORIZONTAL REINFORCING STEEL, PLACED  
IN PLASTIC STIRRUPS, ALTERNATIVELY  
INSIDE  
AND OUTSIDE OF WALL AS SPECIFIED

VERTICAL REINFORCING STEEL PLACED IN  
BETWEEN HORIZONTAL REINFORCING  
STEEL  
AS SPECIFIED.



Stu: 022 372 3109  
[stu@arkform.co.nz](mailto:stu@arkform.co.nz)  
Dave: 021 223 3953  
[dave@arkform.co.nz](mailto:dave@arkform.co.nz)  
Rob: 021 807 692  
[rob@arkform.co.nz](mailto:rob@arkform.co.nz)  
[www.arkform.co.nz](http://www.arkform.co.nz)



Paul Jones:  
021 760 590  
[pauljones@ecoicf.co.nz](mailto:pauljones@ecoicf.co.nz)  
[www.ecoicf.co.nz](http://www.ecoicf.co.nz)