

ECO-BLOCK STANDARD EXPANDED
POLYSTYRENE FORM USING
100mm CONNECTORS

100mm REINFORCED CONCRETE CORE

EXTERIOR BUILDING FINISH
AS SPECIFIED

100mm PLASTIC CONNECTOR.

INTERIOR FINISH
AS SPECIFIED

CUT OUT FORMS
AS NECESSARY TO
MATCH ANCHOR BOLT SPACING

SUBFLOOR

WOOD "I" JOISTS
AS SPECIFIED

JOIST HANGER

LEDGER BOARD/WHALING PLATE SECURED
TO WALL WITH ANCHOR BOLTS
AS SPECIFIED

HORIZONTAL REINFORCING STEEL, PLACED
IN PLASTIC STIRRUPS, ALTERNATIVELY
INSIDE
AND OUTSIDE OF WALL AS SPECIFIED

VERTICAL REINFORCING STEEL PLACED IN
BETWEEN HORIZONTAL REINFORCING
STEEL
AS SPECIFIED.



Stu: 022 372 3109
stu@arkform.co.nz
 Dave: 021 223 3953
dave@arkform.co.nz
 Rob: 021 807 692
rob@arkform.co.nz
www.arkform.co.nz



Paul Jones:
 021 760 590
pauljones@ecoicf.co.nz
www.ecoicf.co.nz