

ECO-BLOCK STANDARD EXPANDED
POLYSTYRENE FORM USING 100mm
CONNECTORS

100mm PLASTIC CONNECTOR.

100mm REINFORCED CONCRETE CORE

INTERIOR FINISH
AS SPECIFIED

BEARING PAD AS
PER SPECIFICATIONS

CUT OUT FORMS
AS NECESSARY TO
MATCH SLAB THICKNESS

TOPPING AS SPECIFIED

HOLLOW CORE PRECAST
SLAB AS SPECIFIED

REINFORCING DOWELS
AS SPECIFIED

HORIZONTAL REINFORCING STEEL,
PLACED IN PLASTIC STIRRUPS,
ALTERNATIVELY INSIDE AND OUTSIDE
OF WALL AS SPECIFIED

VERTICAL REINFORCING STEEL PLACED IN
BETWEEN HORIZONTAL REINFORCING
STEEL AS SPECIFIED.



Stu: 022 372 3109
stu@arkform.co.nz
 Dave: 021 223 3953
dave@arkform.co.nz
 Rob: 021 807 692
rob@arkform.co.nz
www.arkform.co.nz



Paul Jones:
 021 760 590
pauljones@ecoicf.co.nz
www.ecoicf.co.nz