

ECO-BLOCK STANDARD EXPANDED  
POLYSTYRENE FORM USING 100mm  
CONNECTORS

100mm PLASTIC CONNECTOR.

100mm REINFORCED CONCRETE CORE

INTERIOR FINISH  
AS SPECIFIED

EXTERIOR BUILDING FINISH  
AS SPECIFIED

CUT OUT FORMS  
AS NECESSARY TO  
MATCH SLAB THICKNESS

TOPPING AS SPECIFIED

SLAB AS SPECIFIED

BEARING PAD AS  
PER SPECIFICATIONS

REINFORCING DOWELS  
AS SPECIFIED

MINIMUM BEARING ON CONCRETE  
AS SPECIFIED

HORIZONTAL REINFORCING STEEL,  
PLACED IN PLASTIC STIRRUPS,  
ALTERNATIVELY INSIDE AND OUTSIDE  
OF WALL AS SPECIFIED

VERTICAL REINFORCING STEEL PLACED IN  
BETWEEN HORIZONTAL REINFORCING  
STEEL AS SPECIFIED.



Stu: 022 372 3109  
[stu@arkform.co.nz](mailto:stu@arkform.co.nz)  
Dave: 021 223 3953  
[dave@arkform.co.nz](mailto:dave@arkform.co.nz)  
Rob: 021 807 692  
[rob@arkform.co.nz](mailto:rob@arkform.co.nz)  
[www.arkform.co.nz](http://www.arkform.co.nz)



Paul Jones:  
021 760 590  
[pauljones@ecoicf.co.nz](mailto:pauljones@ecoicf.co.nz)  
[www.ecoicf.co.nz](http://www.ecoicf.co.nz)